NEODYMIUM COMMON HF/LF MAGNET COAXIALS

Coherently aligned with precision crafted optimized flux motors, patented Next Generation compression driver technology and smooth transmission interfaces between LF - HF - Horn. 12" or 13.5" models available with 60°x40° coverage horn (CAN123.00TH / CAN143.00TH) or 80° coverage using LF cone (CAN123.00T / CAN143.00T).

- 75 mm (3 in.) LF COPPER VOICE COIL
- 75 mm (3 in.) HF EDGEWOUND CCA VOICE COIL
- 800 W LF PROGRAM POWER HANDLING
- 160 W HF PROGRAM POWER HANDLING
- 45 – 18000 Hz FREQUENCY RANGE
- 1200 Hz RECOMMENDED CROSSOVER
- HYBRID TITANIUM/POLYIMIDE HF DIAPHRAGM
- DOUBLE ALUMINIUM DEMODULATING RINGS

PURE POTENZA

YOUR GLOBAL PARTNER
FOR TRANSDUCERS:
FROM CONCEPT TO DELIVERY

Lavoce
ITALIANA

WWW.LAVOCESPEAKERS.COM
info@lavocespeakers.com
+39 0733 870 840

LAVOCE ITA_Adv AVL ASIA-07-2022_def.indd 1 22/06/22 10:55